

## 电子花样机

Electronic Pattern Sewing Machine

SP-1010BS-HS/MS SP-2210BS-H/M/X  
 SP-1010BS-H/M/X SP-2212BS-H/M/X  
 SP-1510BS-HS/MS SP-1310AS-H/CH侧滑压脚  
 SP-1510BS-H/M/X SP-1310AS-H/FZ 翻转压脚  
 SP-1310AS-HS/MS SP-2212BS-RL三倍旋梭  
 SP-1310AS-H/M/X SP-2212R-H厚料旋梭  
 SP-2210AS-H/M/X



**H** 厚料的缝纫  
Heavy Material

**M** 中厚料的缝纫  
Medium Heavy Material

**X** 极厚料的缝纫  
Super-heavy Material



视频及资料下载  
Video and data download

### 性能优势

- 张力一致的缝制
- 高品质缝纫
- 断线感应器
- 耗电低、高转速、高效能
- 防鸟巢功能（仅限SP-1310/2210DS系列）
- 选购功能装置：侧滑压脚装置、翻转压脚装置
- 花样编辑快速简便
- 强化机针贯穿力
- 优越的扩展改装空间
- 触摸屏内置两种编辑软件
- 电子夹线功能

### Advantages

- Sewing with uniform tension
- High-quality sewing
- Thread broken sensor
- Low power consumption, high speed, high efficiency
- Anti-bird's nest function (only SP-1310/2210DS series)
- Optional device: sliding device, flip flop device
- Pattern edit quick and easy
- Strengthen needle penetration
- Superior expansion and modification space
- In touch screen has 2 editing software
- Disconnection holding function

### 规格 Specification

型号Model	SP-1010BS		SP-1310AS/BS		SP-1510BS		SP-2210AS/BS	
	HS/MS	H/M/X	HS/MS	H/M/X	HS/MS	H/M/X	HS/MS	H/M/X
名称 Name	电子花样机 Electronic Pattern Sewing Machine							
线迹 Line	单针平缝 Single-needle flat seam							
最高缝纫速度 Highest sewing speed	2,800 rpm							
缝制区域(X×Y) Sewing area	100×100 mm		130×100 mm		150×100 mm		200×100 mm	
送布装置 Cloth feeding device	间歇送布 (脉冲马达驱动) Intermittent feeding (driven by pulse motor)							
针距 Stitch length	0.05 - 12.7mm							
最大针数 Max. needle number	20,000针/1个图案(20,000 needles/1 pattern)							
压脚驱动方式 Foot presser driving mode	脉冲马达驱动 Pulse motor drive	气动 Pneumatic	脉冲马达驱动 Pulse motor drive	气动 Pneumatic	脉冲马达驱动 Pulse motor drive	气动 Pneumatic	脉冲马达驱动 Pulse motor drive	气动 Pneumatic
压脚高度 Work Clamp Height	HS/MS:最大25 mm-0 H/M/X:最大30 mm maximum 25 mm maximum 30 mm							
两步压脚 2-step presser foot	一体式压脚 All-in-one presser foot	分离式压脚 Divided presser foot	一体式压脚 All-in-one presser foot	分离式压脚 Divided presser foot	一体式压脚 All-in-one presser foot	分离式压脚 Divided presser foot	一体式压脚 All-in-one presser foot	分离式压脚 Divided presser foot
间歇压脚上升量 Rising amount of intermittent foot presser	22 mm							
间歇压脚行程 Stroke by intermittent presser foot	0或2 - 10 mm (出厂设置: 3mm) 0 or 2 - 10 mm (Factory defaults: 3mm)							
旋梭 Hook	两倍摆梭 Double Shuttle Hook							
扫线装置 Thread Wiper	标准装备 / Standard facility							
切线装置 Cutting device	标准装备 / Standard facility							
数据存储方式 Data storage way	USB							
马达 Motor	AC伺服马达550W / AC servomotor 550W							
机器尺寸 Machine size	1200×800×1250		1200×895×1250		1200×800×1250		1200×900×1300	
包装尺寸 Packing size	1300×900×1350		1300×1000×1350		1300×900×1350		1400×1000×1400	
重量 Weight	150Kg		170Kg		150Kg		170kg	
电源 Power	单相 Single phase 220V, 3相 3-phase 380V							
气压 Air pressure	0.5 Mpa 1.8 L / min							

以上型号仅供参考，详细情况请咨询当地经销商。

The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。

Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.